



003 Adhesive Transfer Tape

General Description

Acrylic based, permanent adhesive on a Havana paper liner. Suitable for a wide range of applications on clean, dry and flat surfaces, including slightly rough and curved surfaces. Not suitable for wet applications.

Application & Use

- Industrial applications
- Carrier lamination applications
- Automotive
- White goods
- Construction
- Thermal insulation

Technical Details

Property	Method	Unit	Typical Value
Carrier Basis Weight	ISO 536	g/m ²	80 ± 4
Carrier Thickness	ISO 534	µm	60 ± 3
Peel Adhesion 180°	AFERA 5001	N/25mm	Min. 20
Shear	AFERA 5012	h	Min. 5
Min. Application Temp	—	°C	0
Service Temperature	—	°C	-15 / +80
Laminate Thickness	ISO 534	µm	50 ± 3

Shelf Life & Storage Conditions

12 months when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C ± 3 °C with a relative humidity of 50% ± 20%.

All information and recommendations about products are based on our existing knowledge and experience but do not mean a guarantee or warranty. As the products are used for different applications we recommend checking suitability of product prior to use. All information is subject to change without notice. End user is obliged to verify the above information before using the material.