



664 Adhesive Tape

General Description

664 is a transparent polyester film coated on both sides with a high coat weight of modified acrylic adhesive. The tape is protected by a siliconised paper release liner.

Key Features

- High adhesive coat weight
- Very good resistance to UV light, chemicals and solvents
- Very good resistance to temperature variations
- Outstanding long term adhesion to metal, paint and high energy plastics
- Good long term adhesion to low energy surfaces
- Suitable for rough or textured surfaces

Technical Details

Property	Value
Carrier	Polyester film, 0.012 mm thick
Release Liner	Amber glassine, 90 gsm
Adhesive	Modified acrylic
Tape Thickness	0.21 mm
Adhesive Strength (20 min)	1200 N/m
Adhesive Strength (24 hr)	1600 N/m
Static Shear @ 23°C	> 400 hours
Static Shear @ 70°C	> 1 hour
Temperature Resistance	-40°C to +160°C (short term to +180°C)
Application Temperature	> 15°C
Chemical Resistance	Resistant to most oils, grease, fuels, aliphatic solvents, weak acids, salts and alkalis

Storage

Store in cool conditions in original packaging away from direct sunlight or heat sources.

All information and recommendations about products are based on our existing knowledge and experience but do not mean a guarantee or warranty. As the products are used for different applications we recommend checking suitability of product prior to use. All information is subject to change without notice. End user is obliged to verify the above information before using the material.